



The GLOBE Program and Software Based Telemetry Processing

Steve Duran
Code 514.2
Data Capture Systems Section
Goddard Space Flight Center
NASA, USA
Spetember 27, 1995



AGENDA



- Overview
- Hardware
- Software
 - TDRSS Forward Link Software
 - TDRSS Return Link Software
- Current Performance Results
- NASA Head Quarters Demo
- Current User's



Overview




- Used Commercial Off The Shelf (COTS) S-bus card to provide a telemetry interface between a SUN Workstation and NASA Communications (NASCOM)
- Designed, implemented, and tested software to perform both forward and return link data processing
- Applied telemetry processing system to GLOBE project



Overview





SCU XMTR = Student Communications Unit Transmitter

SCU RCVR = Student Communications Unit Receiver

TDRSS FDLS = Tracking and Data Relay Satellite System Forward Link System TDRSS RTLS = Tracking and Data Relay Satellite System Return Link System

NOAA FSL = Forecast Systems Laboratory


WSGT/STGT = White Sands Ground Terminal



HARDWARE



- COTS S-bus Digital Signal Processor (DSP) card with a Xilinx Field Programmable Gate Array (FPGA)
 - One Input or Output Channel per DSP card
- COTS RS-422 to TTL Transceiver
 - Provides RS-422 interface to S-bus DSP card
- COTS SUN Workstation






Software




TDRSS Forward Link Software for GLOBE

- Data Formatter
- CCSDS Compliant Convolutional Encoder
- NASCOM TDRSS/MDM Blocker
- Software to transmit blocked files through S-bus DSP card

Step 1



Step 2






Software



TDRSS Return Link Software Software Front End Block Diagram (Workstation Version)






Software



Software Front End Block Diagram (PC Version for GLOBE) Forward Link - TDRSS MA - Broadcast Files to Schools

STEL's TDRSS Receiver





Current Performance Results



Software Front End


- 50 MHz SPARCclassic
 - up to 500 kbps
- SPARC 5 w/ 70 MHz microSPARC Processor
 - up to 1 Mbps
- 25 MHz 486SX (lap top PC)
 - up to 95 kbps



NASA HQ Demo



- 1) Forward link transmission from GSFC to TDRS-E.
- 1A) "Broadcast" signal from TDRS-E received by STEL engineers at Reston, VA.
- 1B) "Broadcast" signal from TDRS-E received by STEL engineers on the roof NASA HQ, DC.
- 2) Return link data flow from transmitter on the roof of the NASA HQ building in DC.
- 3) Return link data flow from the transmitter at STEL in Reston, VA.





Current User's



- ACE (Advanced Composition Explorer) Ground System
- EUVE (Extreme Ultraviolet Explorer) Ground System
- PORTCOM (Portable Communications) (formerly GLOBE)
- Standford Telecom
- PTP (Programmable Telemetry Processor, NASA, GSFC)
- Landsat 7 Ground System
- TRW for EOS (Earth Observing System)
 Ground System